

## WOVEN MESH SELECTOR

DIAMETER OF WIRE		WIDTH OF OPENING		OPEN AREA	APPROXIMATE WEIGHTS POUNDS PER 100 SQUARE FEET
Inches	Mm.	Inches	Mm.		
<b>1" Mesh Center to Center of wire</b>					
.148	3.76	.8520	21.64	72.6	141.7
.135	3.43	.8560	21.97	74.8	117.7
.120	3.05	.8800	22.35	77.4	92.8
.105	2.67	.8950	22.73	80.1	71.0
.092	2.34	.9080	23.06	82.4	54.4
.080	2.03	.9200	23.37	84.6	41.1
.063	1.60	.9370	23.80	87.8	25.5
<b>3/4" Mesh Center to Center of wire</b>					
.135	3.43	.6150	15.62	67.2	158.1
.120	3.05	.6300	16.00	70.5	124.4
.105	2.67	.6450	16.38	73.9	95.0
.092	2.34	.6580	16.71	76.9	72.8
.080	2.03	.6700	17.02	79.8	54.9
.072	1.83	.6780	17.22	81.7	44.5
.063	1.60	.6870	17.45	83.9	34.0
<b>5/8" Mesh Center to Center of wire</b>					
.135	3.43	.4900	12.45	61.5	191.0
.120	3.05	.5050	12.83	65.3	150.2
.105	2.67	.5200	13.21	69.2	114.5
.092	2.34	.5330	13.54	72.7	87.9
.080	2.03	.5450	13.84	76.0	66.1
.072	1.83	.5530	14.05	78.3	53.5
.063	1.60	.5620	14.27	80.9	40.9
<b>2 Mesh</b>					
.135	3.43	.3650	9.27	53.3	241.7
.120	3.05	.3800	9.65	57.8	189.6
.105	2.67	.3950	10.03	62.4	144.2
.092	2.34	.4080	10.36	66.6	110.2
.080	2.03	.4200	10.67	70.6	83.0
.072	1.83	.4280	10.87	73.3	67.1
.063	1.60	.4370	11.10	76.4	51.2
.054	1.37	.4460	11.33	79.6	37.6
.047	1.19	.4530	11.51	82.1	28.4
<b>3 Mesh</b>					
.120	3.05	.2133	5.41	40.8	293.9
.105	2.67	.2283	5.79	46.8	222.0
.092	2.34	.2413	6.12	52.3	168.7
.080	2.03	.2533	6.43	57.6	126.4
.072	1.83	.2613	6.63	61.3	101.9
.063	1.60	.2703	6.86	65.6	77.6
.054	1.37	.2793	7.09	70.1	56.7
.047	1.19	.2863	7.26	73.6	42.8
<b>4 Mesh</b>					
.135	3.43	.1150	2.92	21.2	503.8
.120	3.05	.1300	3.30	27.0	388.6
.105	2.67	.1450	3.68	33.6	306.2
.092	2.34	.1580	4.01	39.9	231.0
.080	2.03	.1700	4.32	46.2	172.1
.072	1.83	.1780	4.52	50.7	138.2
.063	1.60	.1870	4.75	56.0	104.8
.054	1.37	.1960	4.98	61.5	76.4
.047	1.19	.2030	5.16	65.9	57.6
.041	1.04	.2090	5.31	69.9	43.6
.035	.89	.2150	5.46	74.0	31.7
<b>6 Mesh</b>					
.092	2.34	.0747	1.91	20.2	352.8
.080	2.03	.0867	2.21	27.2	259.1
.072	1.83	.0947	2.41	32.5	216.9
.063	1.60	.1037	2.64	38.9	163.0
.054	1.37	.1127	2.87	46.0	117.0
.047	1.19	.1197	3.05	51.8	88.2
.041	1.04	.1257	3.20	57.2	66.5
.035	.89	.1317	3.35	62.7	48.1
.032	.81	.1347	3.43	65.6	40.0
.028	.71	.1387	3.53	69.6	30.5
<b>8 Mesh</b>					
.072	1.83	.0530	1.35	18.0	291.1
.063	1.60	.0620	1.58	24.6	216.3
.054	1.37	.0710	1.80	32.3	162.7
.047	1.19	.0780	1.98	38.9	120.9
.041	1.04	.0840	2.13	45.2	90.6
.035	.89	.0900	2.29	51.8	65.1
.032	.81	.0930	2.36	55.4	54.1
.028	.71	.0970	2.46	60.2	41.1
.025	.64	.1000	2.54	64.0	32.6
.023	.58	.1020	2.59	66.6	27.5
.020	.51	.1050	2.67	70.6	20.7

## SPACE MESH SELECTOR

DIAMETER OF WIRE		OPEN AREA	APPROXIMATE WEIGHTS POUNDS PER SQUARE FOOT
Inches	Mm.		
<b>1 1/2" Opening</b>			
.162	4.11	81.5	1.02
.148	3.76	82.8	.85
.135	3.43	84.2	.72
.120	3.05	85.7	.57
<b>1 1/4" Opening</b>			
.225	5.72	71.8	2.22
.162	4.11	78.4	1.20
.148	3.76	79.9	1.01
.135	3.43	81.5	.85
.120	3.05	83.2	.68
.105	2.67	85.1	.52
<b>1 1/8" Opening</b>			
.162	4.11	76.4	1.32
.148	3.76	78.1	1.11
.135	3.43	79.7	.93
.120	3.05	81.7	.74
.105	2.67	83.7	.58
.092	2.34	85.5	.45
<b>1" Opening</b>			
.162	4.11	74.0	1.46
.148	3.76	75.9	1.23
.135	3.43	77.6	1.04
.120	3.05	79.7	.83
.105	2.67	81.9	.64
.092	2.34	83.9	.50
.080	2.03	85.7	.38
<b>7/8" Opening</b>			
.162	4.11	71.2	1.64
.148	3.76	73.5	1.38
.135	3.43	75.1	1.17
.120	3.05	77.3	.93
.105	2.67	79.7	.72
.092	2.34	81.9	.56
.080	2.03	83.9	.43
<b>3/4" Opening</b>			
.162	4.11	67.6	1.87
.148	3.76	69.8	1.58
.135	3.43	71.8	1.33
.120	3.05	74.3	1.07
.105	2.67	76.9	.83
.092	2.34	79.3	.65
.080	2.03	81.7	.50
<b>5/8" Opening</b>			
.162	4.11	63.1	2.18
.148	3.76	65.4	1.85
.135	3.43	67.6	1.56
.120	3.05	70.3	1.25
.105	2.67	73.4	.98
.092	2.34	76.0	.76
.080	2.03	78.6	.58
.072	1.83	80.4	.48
.063	1.60	82.5	.37
<b>1/2" Opening</b>			
.207	5.26	49.8	4.04
.162	4.11	57.1	2.61
.148	3.76	59.5	2.22
.135	3.43	62.0	1.88
.120	3.05	65.0	1.51
.105	2.67	68.3	1.18
.092	2.34	71.3	.93
.080	2.03	74.3	.71
.072	1.83	76.4	.58
.063	1.60	78.9	.45
<b>3/8" Opening</b>			
.162	4.11	48.7	3.27
.148	3.76	51.4	2.79
.135	3.43	54.1	2.37
.120	3.05	57.4	1.92
.105	2.67	61.0	1.51
.092	2.34	64.5	1.18
.080	2.03	67.9	.91
.072	1.83	70.4	.75
.063	1.60	73.3	.59
.054	1.37	76.4	.44

### The Stanwood Corporation Can Also Supply:

Muffles - Retorts - Heat Treating Baskets - Furnace Fans - Radiant Tubes - Furnace Rolls - Heating Elements - Salt Pats - Generator Retorts - Corrugated Boxes - Serpentine Trays - Custom Designed Fixtures

**930 Columbia Avenue • South Milwaukee, WI 53172**

**414/762.6795 • Fax: 414/762.3663 • Web: www.stanwoodcorp.com**